

Trapping Oracle Server Exceptions

Terminology

Directions: Identify the vocabulary word for each definition below:

1. _____ Each of these has a predefined name. For example, if the error ORA-01403 occurs when no rows are retrieved from the database in a SELECT statement, then PL/SQL raises the predefined exception-name NO_DATA_FOUND.
2. _____ Tells the compiler to associate an exception name with an Oracle error number. That allows you to refer to any Oracle Server exception by name and to write a specific handler for it.
3. _____ Returns character data containing the message associated with the error number
4. _____ Each of these has a standard Oracle error number (ORA-nnnnn) and error message, but not a predefined name. We declare our own names for these so that we can reference these names in the exception section.
5. _____ Returns the numeric value for the error code (You can assign it to a NUMBER variable.)

Try It / Solve It

1. What are the three types of exceptions that can be handled in a PL/SQL block?
2. What is the difference in how each of these three types of exception is handled in the PL/SQL block?
3. Enter and run the following PL/SQL block. Look at the output and answer the following questions:

```
DECLARE
  v_number    NUMBER(6,2) := 100;
  v_region_id wf_world_regions.region_id%TYPE;
  v_region_name wf_world_regions.region_name%TYPE;
BEGIN
  SELECT region_id, region_name INTO v_region_id, v_region_name
  FROM wf_world_regions
  WHERE region_id = 1;
  DBMS_OUTPUT.PUT_LINE('Region: ' || v_region_id ||
    ' is: ' || v_region_name);
  v_number := v_number / 0;
END;
```

- A. What error message is displayed and why ?
- B. Modify the block to handle this exception and re-run your code. Now what happens and why?

C. Modify the block again to change the WHERE clause to region_id = 29. Re-run the block. Now what happens and why?

D. Modify the block again to handle the latest exception and re-run your code.

4. Enter and run the following PL/SQL block. Look at the output and answer the following questions:

```
DECLARE
  CURSOR regions_curs IS
  SELECT * FROM wf_world_regions
  WHERE region_id < 20
  ORDER BY region_id;
  regions_rec regions_curs%ROWTYPE;
  v_count NUMBER(6);
BEGIN
  LOOP
  FETCH regions_curs INTO regions_rec;
  EXIT WHEN regions_curs%NOTFOUND;
  DBMS_OUTPUT.PUT_LINE('Region: ' || regions_rec.region_id ||
    ' Name: ' || regions_rec.region_name);
  END LOOP;
  CLOSE regions_curs;
  SELECT COUNT(*) INTO v_count
  FROM wf_world_regions
  WHERE region_id = 1;
  DBMS_OUTPUT.PUT_LINE('The number of regions is: ' || v_count);
END;
```

A. What happens and why ?

B. Modify the block to handle the exception and re-run your code.

C. Modify the block again to add an OPEN statement for the cursor, and re-run your code. Now what happens and why? Remember that region_id = 1 does not exist.

5. Oracle Server Error:s:

- A. Add an exception handler to the following code to trap the following predefined Oracle Server errors: NO_DATA_FOUND, TOO_MANY_ROWS and DUP_VAL_ON_INDEX.

```
DECLARE
  v_language_id wf_languages.language_id%TYPE;
  v_language_name wf_languages.language_name%TYPE;
BEGIN
  SELECT language_id, language_name
  INTO v_language_id, v_language_name
  FROM wf_languages
  WHERE LOWER(language_name) LIKE '<substring%>'; -- for example 'ab%'
  INSERT INTO wf_languages(language_id, language_name)
  VALUES(80, null);
END;
```

- B. Test your block twice using each of the following language substrings: ba, ce. There are several language_names beginning with “Ba” but none beginning with “Ce”.
- C. Now test your block a third time using substring: al. There is exactly one language_name beginning with “Al”. Note that language_id 80 (Arabic) already exists. Explain the output.
- D. Now (keeping the substring as “al”) add a non_predefined exception handler to trap the ORA-01400 exception. Name your exception e_null_not_allowed. Rerun the code and observe the results.

Extension exercise

1. In preparation for this exercise, run the following SQL statement to create an error-logging table:

```
CREATE TABLE error_log (who          VARCHAR2(30),
                        when         DATE,
                        error_code    NUMBER(6),
                        error_message VARCHAR2(255));
```

Modify your PL/SQL block from question 5 to remove the four explicit exception handlers, replacing them with a single WHEN OTHERS handler. The handler should INSERT a row into the error_log table each time an exception is raised and handled. The row should consist of the Oracle username (who), when the error was raised (when) and the SQLCODE and SQLERRM of the exception. Test your block several times, with different data values to raise each of the four kinds of exception handled in the block. Finally, SELECT from the error-logging table to check that the rows have been inserted.