


Using Variables in PL/SQL

What Will I Learn?

In this lesson, you will learn how to:


- Describe the use of variables in PL/SQL
- Identify the syntax for variables in PL/SQL
- Declare and initialize variables in PL/SQL
- Assign new values to variables in PL/SQL





Why Learn It?

You use variables to store and manipulate data. In this lesson, you learn how to declare and initialize variables in the declarative section of a PL/SQL block. With PL/SQL, you can declare variables and then use them in SQL and procedural statements.





Tell Me/Show Me

Use of Variables

You can use variables for:

- Temporary storage of data
- Manipulation of stored values
- Reusability



Tell Me/Show Me

Handling Variables in PL/SQL

Variables are:

- Declared and initialized in the declarative section
- Used and assigned new values in the executable section

Variables can be:

- Passed as parameters to PL/SQL subprograms
- Assigned to hold the output of a PL/SQL subprogram

Tell Me/Show Me

Declaring Variables

- All PL/SQL variables must be declared in the declaration section before referencing them in the PL/SQL block.
- The purpose of a declaration is to allocate storage space for a value, specify its data type, and name the storage location so that you can reference it.
- You can declare variables in the declarative part of any PL/SQL block, subprogram, or package.



Tell Me/Show Me

Declaring Variables: Syntax

Tell Me/Show Me

Declaring Variables: Syntax (continued)

Tell Me/Show Me

Initializing Variables

Variables are assigned a memory location inside the DECLARE section. Variables can be assigned a value at the same time. This process is called initializing.

```
DECLARE
count  INTEGER := 0;
BEGIN
count  := count + 1;
        DBMS_OUTPUT.PUT_LINE(count);
END;
```



Tell Me/Show Me

Declaring and Initializing Variables: Examples

```
DECLARE
  fam_birthdate      DATE;
  fam_size           NUMBER(2) NOT NULL := 10;
  fam_location       VARCHAR2(13) := 'Florida';
  fam_bank           CONSTANT NUMBER := 50000;
  fam_population     INTEGER;
  fam_name           VARCHAR2(20) DEFAULT 'Roberts';
  fam_party_size     CONSTANT PLS_INTEGER := 20;
```



Tell Me/Show Me

Declaring and Initializing Variables: Examples (continued)

```
DECLARE
  v_emp_hiredate      DATE;
  v_emp_deptno       NUMBER(2) NOT NULL := 10;
  v_location         VARCHAR2(13) := 'Atlanta';
  c_comm             CONSTANT NUMBER := 1400;
  v_population       INTEGER;
  v_book_type        VARCHAR2(20) DEFAULT 'fiction';
  v_artist_name      VARCHAR2(50);
  v_firstname        VARCHAR2(20) := 'Rajiv';
  v_lastname         VARCHAR2(20) DEFAULT 'Kumar';
  c_display_no       CONSTANT PLS_INTEGER := 20;
  ...
```

Tell Me/Show Me

Assigning Values in the Executable Section

After a variable is declared, you can use it in the executable section of a PL/SQL block. For example, in the following block, the variable `v_myname` is declared in the declarative section of the block. You can access this variable in the executable section of the same block. What do you think the block will print?

```
DECLARE
  v_myname VARCHAR2(20);
BEGIN
  DBMS_OUTPUT.PUT_LINE('My name is: ' || v_myname);
  v_myname := 'John';
  DBMS_OUTPUT.PUT_LINE('My name is: ' || v_myname);
END;
```



Tell Me/Show Me

Assigning Values in the Executable Section (continued)

In this example, the value `John` is assigned to the variable in the executable section. The value of the variable is concatenated with the string `My name is:` . The output is:

```
My name is:  
My name is:  John  
  
Statement process.
```



Tell Me/Show Me

Assigning Values in the Executable Section

In this block, the variable `v_myname` is declared and initialized in the declarative section. `v_myname` holds the value `John` after initialization. This value is manipulated in the executable section of the block.

```
DECLARE
  v_myname VARCHAR2(20) := 'John';
BEGIN
  v_myname := 'Steven';
  DBMS_OUTPUT.PUT_LINE('My name is: ' || v_myname);
END;
```

The output is:

```
My name is: Steven
Statement processed.
```



Tell Me/Show Me

Passing Variables as Parameters to PL/SQL Subprograms

Parameters are values passed to a program by the user or by another program to customize the program.

In PL/SQL, subprograms can take parameters. You can pass variables as parameters to procedures and functions.

In the following example, the parameter `v_date` is being passed to the procedure `PUT_LINE`, which is part of the package, `DBMS_OUTPUT`.

```
DECLARE
  v_date VARCHAR2(30);
BEGIN
  SELECT TO_CHAR(SYSDATE) INTO v_date FROM dual;
  DBMS_OUTPUT.PUT_LINE(v_date);
END;
```



Tell Me/Show Me

Assigning Variables to PL/SQL Subprogram Output

You can use variables to hold the value that is returned by a function.

```
--function to return number of characters in string
FUNCTION num_characters (p_string IN VARCHAR2) RETURN INTEGER IS
    v_num_characters INTEGER;
BEGIN
    SELECT LENGTH(p_string) INTO v_num_characters FROM dual;
    RETURN v_num_characters;
END;
```

```
--anonymous block: assign variable to function output
DECLARE
    v_length_of_string INTEGER;
BEGIN
    v_length_of_string := num_characters('Oracle Corporation');
    DBMS_OUTPUT.PUT_LINE(v_length_of_string);
END;
```


Try It/Solve It

Terminology

Key terms used in this lesson include:

Variables


Parameters



Summary

In this lesson, you have learned how to:

- List the uses of variables in PL/SQL
- Identify the syntax for variables in PL/SQL
- Declare and initialize variables in PL/SQL
- Assign new values to variables in PL/SQL



Try It/Solve It

The exercises in this lesson cover the following topics:

- Listing the uses of variables in PL/SQL
- Determining valid variable declarations in PL/SQL
- Declaring and initializing variables in PL/SQL
- Assigning new values to variables in PL/SQL

