


# Using Explicit Cursor Attributes

## What Will I Learn?

In this lesson, you will learn to:


- Define a record structure using the `%ROWTYPE` attribute
- Create PL/SQL code to process the rows of an active set using record types in cursors
- Retrieve information about the state of an explicit cursor using cursor attributes




## Why Learn It?

One of the reasons to use explicit cursors is that they give you greater programmatic control when handling your data. This lesson discusses techniques for using explicit cursors more effectively.

- Cursor records enable you to declare a single variable for all the selected columns in a cursor.
- Cursor attributes enable you to retrieve information about the state of your explicit cursor.



## Tell Me/Show Me



### Cursors and Records

The cursor in this example is based on a SELECT statement that retrieves only two columns of each table row:

```
DECLARE
  v_emp_id      employees.employee_id%TYPE;
  v_last_name   employees.last_name%TYPE;
  CURSOR emp_cursor IS
    SELECT employee_id, last_name
       FROM employees
       WHERE department_id =30;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor
       INTO v_emp_id, v_last_name;
    ...
  
```

What if it retrieved six columns .. or seven, or eight, or twenty?

# Tell Me/Show Me

## Cursors and Records

This cursor retrieves whole rows of EMPLOYEES:

```
DECLARE
  v_emp_id          employees.employee_id%TYPE;
  v_first_name     employees.first_name%TYPE;
  v_last_name      employees.last_name%TYPE;
  ...
  v_department_id  employees.department_id%TYPE;
  CURSOR emp_cursor IS
    SELECT * FROM employees
      WHERE department_id =30;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor
      INTO v_emp_id, v_first_name, v_last_name ...
          v_department_id;
    ...
  
```

Messy and long-winded, isn't it?



# Tell Me/Show Me

## Cursors and Records

Compare the following snippets of code. What differences do you see?

```
DECLARE
  v_emp_id          ...;
  v_first_name     ...;
  ...
  v_department_id  ...:
  CURSOR emp_cursor IS
    SELECT * FROM employees
    WHERE department_id =30;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor
    INTO v_emp_id, v_first_name,
    ... v_department_id;
  ...
```

```
DECLARE
  CURSOR emp_cursor IS
    SELECT * FROM employees
    WHERE department_id =30;
  v_emp_record
    emp_cursor%ROWTYPE;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor
    INTO v_emp_record;
  ...
```



# Tell Me/Show Me

## Cursors and Records

The code on the right uses %ROWTYPE to declare a **record** structure based on the cursor. A record is a composite data type in PL/SQL.

### Variables


```
DECLARE
  v_emp_id          ...;
  v_first_name     ...;
  ...
  v_department_id ...:
  CURSOR emp_cursor IS
    SELECT * FROM employees
    WHERE department_id =30;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor
    INTO v_emp_id, v_first_name,
    ... v_department_id;
  ...
```

### Records

```
DECLARE
  CURSOR emp_cursor IS
    SELECT * FROM employees
    WHERE department_id =30;
  v_emp_record
    emp_cursor%ROWTYPE;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor
    INTO v_emp_record;
  ...
```

## Tell Me/Show Me

### Structure of a PL/SQL Record:



A record is a composite data type, consisting of a number of fields each with their own name and data type.

You reference each field by dot-prefixing its field-name with the record-name.

`%ROWTYPE` declares a record with the same fields as the cursor on which it is based.



# Tell Me/Show Me

## Structure of *cursor\_name*%ROWTYPE:

```
DECLARE
  CURSOR emp_cursor IS
    SELECT employee_id, last_name, salary FROM employees
       WHERE department_id =30;
  v_emp_record emp_cursor%ROWTYPE;
  ...
```

<code>v_emp_record.employee_id</code>	<code>v_emp_record.last_name</code>	<code>v_emp_record.salary</code>
---------------------------------------	-------------------------------------	----------------------------------

100	King	24000
-----	------	-------



# Tell Me/Show Me

## Cursors and %ROWTYPE

`%ROWTYPE` is convenient for processing the rows of the active set because you can simply fetch into the record.

```
DECLARE
  CURSOR emp_cursor IS
    SELECT * FROM employees
    WHERE department_id =30;
  v_emp_record emp_cursor%ROWTYPE;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor INTO v_emp_record;
    EXIT WHEN emp_cursor%NOTFOUND;
    DBMS_OUTPUT.PUT_LINE(v_emp_record.employee_id || ' - '
      || v_emp_record.last_name);
  END LOOP;
  CLOSE emp_cursor;
END;
```



# Tell Me/Show Me

## Cursors and %ROWTYPE: Another Example

```
DECLARE
  CURSOR emp_dept_cursor IS
    SELECT first_name, last_name, department_name
       FROM employees e, departments d
       WHERE e.department_id = d.department_id;
  v_emp_dept_record    emp_dept_cursor%ROWTYPE;
BEGIN
  OPEN emp_dept_cursor;
  LOOP
    FETCH emp_dept_cursor INTO v_emp_dept_record;
    EXIT WHEN emp_dept_cursor%NOTFOUND;
    DBMS_OUTPUT.PUT_LINE(v_emp_dept_record.first_name
      || ' - ' || v_emp_dept_record.last_name
      || ' - ' || v_emp_dept_record.department_name);
  END LOOP;
  CLOSE emp_dept_cursor;
END;
```



# Tell Me/Show Me

## Explicit Cursor Attributes

As with implicit cursors, there are several attributes for obtaining status information about an explicit cursor. When appended to the cursor variable name, these attributes return useful information about the execution of a cursor manipulation statement.

Attribute	Type	Description
<code>%ISOPEN</code>	Boolean	Evaluates to <code>TRUE</code> if the cursor is open
<code>%NOTFOUND</code>	Boolean	Evaluates to <code>TRUE</code> if the most recent fetch did not return a row
<code>%FOUND</code>	Boolean	Evaluates to <code>TRUE</code> if the most recent fetch returned a row; opposite of <code>%NOTFOUND</code>
<code>%ROWCOUNT</code>	Number	Evaluates to the total number of rows <code>FETChED</code> so far



## Tell Me/Show Me

### `%ISOPEN` Attribute

You can fetch rows only when the cursor is open. Use the `%ISOPEN` cursor attribute before performing a fetch to test whether the cursor is open.

`%ISOPEN` returns the status of the cursor: `TRUE` if open and `FALSE` if not.

Example:

```
IF NOT emp_cursor%ISOPEN THEN
    OPEN emp_cursor;
END IF;
LOOP
    FETCH emp_cursor...
```



## Tell Me/Show Me

### **%ROWCOUNT and %NOTFOUND Attributes**

Usually the `%ROWCOUNT` and `%NOTFOUND` attributes are used in a loop to determine when to exit the loop.

Use the `%ROWCOUNT` cursor attribute for the following:

- To process an exact number of rows
- To count the number of rows fetched so far in a loop and/or determine when to exit the loop

Use the `%NOTFOUND` cursor attribute for the following:

- To determine whether the query found any rows matching your criteria
- To determine when to exit the loop



## Tell Me/Show Me

### Example of %ROWCOUNT and %NOTFOUND

This example shows how you can use %ROWCOUNT and %NOTFOUND attributes for exit conditions in a loop.

```
DECLARE
  CURSOR emp_cursor IS
    SELECT employee_id, last_name FROM employees;
  v_emp_record  emp_cursor%ROWTYPE;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor INTO v_emp_record;
    EXIT WHEN emp_cursor%ROWCOUNT > 10 OR emp_cursor%NOTFOUND;
    DBMS_OUTPUT.PUT_LINE(v_emp_record.employee_id
      || ' ' || v_emp_record.last_name);
  END LOOP;
  CLOSE emp_cursor;
END;
```



## Tell Me/Show Me

### Explicit Cursor Attributes in SQL Statements

You cannot use an explicit cursor attribute directly in an SQL statement. The following code returns an error:

```
DECLARE
  CURSOR emp_cursor IS
    SELECT employee_id, salary FROM employees
    ORDER BY SALARY DESC;
  v_emp_record  emp_cursor%ROWTYPE;
  v_count      NUMBER;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH emp_cursor INTO v_emp_record;
    EXIT WHEN emp_cursor%NOTFOUND;
    INSERT INTO top_paid_emps
      (employee_id, rank, salary)
    VALUES
      (v_emp_record.employee_id, emp_cursor%ROWCOUNT,
       v_emp_record.salary);
  ...
```

# Tell Me/Show Me

## Terminology

Key terms used in this lesson include:


Record

%ROWTYPE

%ISOPEN

%ROWCOUNT


%NOTFOUND



## Summary

In this lesson, you learned to:

- Define a record structure using the `%ROWTYPE` attribute
- Create PL/SQL code to process the rows of an active set using record types in cursors
- Retrieve information about the state of an explicit cursor using cursor attributes



## Try It/Solve It

The exercises in this lesson cover the following topics:

- Defining a record structure using the `%ROWTYPE` attribute
- Creating PL/SQL code to process the rows of an active set using record types in cursors
- Retrieving information about the state of an explicit cursor using cursor attributes

